


M | Transparent PRODUCT SPECIFICATIONS


STYLE NUMBER	802Q6
PRODUCT TYPE	Modular
CONSTRUCTION	Multi-Level Pattern Loop
FIBER TYPE	Eco Solution Q® Nylon
DYE METHOD	100% Solution Dyed
PRIMARY BACKING	Non-Woven Synthetic
SECONDARY BACKING	Ecworx

	US Units	Metric Units
PRODUCT SIZE	12 inches x 48 inches	30.48 cm x 121.92 cm
GAUGE	1/12 inches	47.24 per 10 cm
STITCHES	12 per inches	46 per 10 cm
FINISHED PILE THICKNESS	0.092 inches	2.34 mm
AVERAGE DENSITY	8609 oz/yd ³	
TOTAL THICKNESS	0.254 inches	6.45 mm
TUFTED YARN WEIGHT	22 oz/yd ²	745.9 g/m ²


Installation Methods




Monolithic




Brick



Herringbone



Stagger



Offset

Performance Testing

PILL TEST	Pass
RADIANT PANEL	Class I
NBS SMOKE	Less than 450
ELECTROSTATIC PROPENSITY	Less than 3.5 kv
CRI GREENLABEL PLUS	GLP9968
ADA COMPLIANCE	>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes