

# B | Gray Dream PRODUCT SPECIFICATIONS

|                          |                          |
|--------------------------|--------------------------|
| <b>STYLE NUMBER</b>      | 801F9                    |
| <b>PRODUCT TYPE</b>      | Broadloom                |
| <b>CONSTRUCTION</b>      | Multi-Level Pattern Loop |
| <b>FIBER TYPE</b>        | Solution Q Nylon         |
| <b>DYE METHOD</b>        | 100% Solution Dyed       |
| <b>PRIMARY BACKING</b>   | Synthetic                |
| <b>SECONDARY BACKING</b> | Ultraloc (R)             |

|                                    | <b>US Units</b>         | <b>Metric Units</b>     |
|------------------------------------|-------------------------|-------------------------|
| <b>PRODUCT SIZE</b>                | 12 ft                   | 3.66 m                  |
| <b>GAUGE</b>                       | 1/10 inches             | 39.37 per 10 cm         |
| <b>STITCHES</b>                    | 12 per inches           | 46 per 10 cm            |
| <b>FINISHED PILE THICKNESS</b>     | 0.091 inches            | 2.31 mm                 |
| <b>AVERAGE DENSITY</b>             | 8703 oz/yd <sup>3</sup> |                         |
| <b>TOTAL THICKNESS</b>             | 0.267 inches            | 6.78 mm                 |
| <b>TUFTED YARN WEIGHT</b>          | 22 oz/yd <sup>2</sup>   | 745.9 g/m <sup>2</sup>  |
| <b>INSTALLATION PATTERN REPEAT</b> | 1.2 ft W X 2 ft L       | 36.58 cm W X 60.96 cm L |

## Performance Testing

|                                 |   |
|---------------------------------|---|
| <b>PILL TEST</b>                | Pass  |
| <b>RADIANT PANEL</b>            | Class I   |
| <b>NBS SMOKE</b>                | Less than 450   |
| <b>ELECTROSTATIC PROPENSITY</b> | Less than 3.5 kv  |
| <b>CRI GREENLABEL PLUS</b>      | GLP8472   |
| <b>ADA COMPLIANCE</b>           | >0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes |