

# M | Teal Tranquility

## PRODUCT SPECIFICATIONS

<b>STYLE NUMBER</b>	801G4
<b>PRODUCT TYPE</b>	Modular
<b>CONSTRUCTION</b>	Multi-Level Pattern Loop
<b>FIBER TYPE</b>	Eco Solution Q® Nylon
<b>DYE METHOD</b>	100% Solution Dyed
<b>PRIMARY BACKING</b>	Non-Woven Synthetic
<b>SECONDARY BACKING</b>	Ecoworx


### US Units

<b>PRODUCT SIZE</b>	24 inches x 24 inches
<b>GAUGE</b>	1/10 inches
<b>STITCHES</b>	10 per inches
<b>FINISHED PILE THICKNESS</b>	0.099 inches
<b>AVERAGE DENSITY</b>	5818 oz/yd <sup>3</sup>
<b>TOTAL THICKNESS</b>	0.224 inches
<b>TUFTED YARN WEIGHT</b>	16 oz/yd <sup>2</sup>


### Metric Units

60.96 cm x 60.96 cm
39.37 per 10 cm
41 per 10 cm
2.51 mm
5.69 mm
542.5 g/m <sup>2</sup>


## Installation Methods




1/4 Turn




Random



Monolithic



Brick



Interactive Patterning

## Performance Testing

<b>PILL TEST</b>	Pass
<b>RADIANT PANEL</b>	Class I
<b>NBS SMOKE</b>	Less than 450
<b>ELECTROSTATIC PROPENSITY</b>	Less than 3.5 kv
<b>CRI GREENLABEL PLUS</b>	GLP9968
<b>ADA COMPLIANCE</b>	>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes